
	MARK	L	A	S	USED FOR
	(A)	4000	266	8 5	REWINDER APRON GUIDE
	В	4700	266	8 5	EXIT GUIDE TAIL END HOLDER ROLL
	C	5000	266	8 5	EXIT GUIDE IRONING ROLL DRIVE SIDE
	D	3600	266	8 5	EXIT GUIDE IRONING ROLL OPER. SIDE
	E	6600	△ 311 △ 363	130	EXIT GUIDE SQUEEZING ROLL ARM DRIVE SIDE
	F	2450	A 363	130	EXIT GUIDE SQUEEZING ROLL ARM OPER. SIDE
	G	6200	266	8 5	FEED BACK GAUGE GUARD
	H	7000	<u>181</u>	5 0	EXIT GUIDE SLIDE FRAME DRIVE SIDE
	(1)	6800	266	8 5	ROTARY SHEAR FRAME
2	J	2000	181	5 0	EXIT GUIDE SLIDE FRAME OPE. SIDE



PUSH PULL CABLE

	·Design :	The product itself shall be of intrinsically safe
ı		design. When it is difficult to design so, a safety device (s) should be added to secure the safety.
	·Safety plates:	To assure the safety, safety precautions (Danger,
		warning, caution or notice) shall be clearly
١		indicated by means of an aluminium plate (set screw
ı		type) on the parts where such safety precaution is
		regarded as necassary.
		The indication shall, in principle, conform to ANSI

Interaction services and are services and are services a part of that product. Hence, a separate section for safety shall be provided to take adequate measures

for PL Law.

Due responsibility shall be taken for a personal injury or physical damage caused by a defect of the product.

"Supplier" shall obtain at its costs and expenses all licenses, permits, formalities or other approvals from supplier's Government or and participation of the contract. It is expressly agreed herein that "Supplier' shall be responsible for any matter (including but not limited to penalties claimed by the relevant authorities) arising out of non fulfilment of the obligations hereabove.

RUST PREVENTIVE OIL APPLIED (1) PROCESSING EXPOSURE SIDE

: NP-10 APPLIED
(2) OIL BATH : 1' st NP-10 APPLIED 2' nd NP-20 APPLIED

								- VI
MARK		PARTI	CULARS	MATERIAL	NO. REQ.	MASS (kg)	REMARKS	PART NO.
A	PUSH	PULL	CABLE					100
В	PUSH	PULL	CABLE					101
С	PUSH	PULL	CABLE					102
D	PUSH	PULL	CABLE					103
E	PUSH	PULL	CABLE					104
F	PUSH	PULL	CABLE					105
G	PUSH	PULL	CABLE					106
Н	PUSH	PULL	CABLE					107
I	PUSH	PULL	CABLE					108
J	PUSH	PULL	CABLE					131

One electrophotographically repoducible copy of drawing and CAN-DATA to be delivered should be submitted immediately after conclusion of a contract.
 To be submitted to (HI's Procurement Department.

To be submitted to INI's Procurement Department.

2 the drawings to be delivered should have the following
described or attached.

(1) HII's mort Mac, classification Mo., assembly No., part No.,
and Component No.

(2) Inspection method for assuring performance
(3) GO, required oil amount, mass
(4) instruction manual (Safety) item shall be described),
components list and recommended space parts list,
(5) Deviation—Presentation of AutoCAD or WiccoCADAM by
the floopy disk.

10 recommended in the CADAM of AutoCAD or WiccoCADAM by
the floopy disk.

3. One reproducible copy of the IHI's designated statement for 3. One reproducible copy of the IBI's designated statement for delivery and shipping specification should be submitted. (The from will be supplied wis 1856 Precuring Group.)

The from delivery fuelses otherwise specified and at delivery: at the first time to the YEC Precuring Group.

And at the second time to the Material Control Group.

(Each time the detailed statement is to be partially altered, it hand be revised and submitted.)

A. Attacking a tag
At delivery a tag shall be prepared per line of the detailed
statement, and lied on the actual product.
In this respect, lift will supply its designated tag for the
contract work. You are requested to write necessary matters on
that tag, and then to lie it on the product. Therefore, you
about do contract the Precenting Group to confirm it beforehand.

The document to be submitted shall be written in English.
 It may, however, be in both Japanese and English.

6. The applicable unit shall be SI unit.

7. Notes: (1) Two or more sheets of drawing are to be delivered, the drawing sizes must be unified.
(2) A space (50m x 50m) for document stamp should be left at the upper part of the right lower title

column.

For laws, regulations and standards, Japanese domestic laws, regulation and standards shall apply.

2. The painting color shall be a manufacture's standard color.

For the painting color, the supplied color sample shall apply.

For the painting color, conform to IIII drawing M316012435.


3. For the guarantee period, the general contract or the order requisition shall apply.

4. Note: Then a manufacture is to change the design (including the internal configuration) of the product manufactured so far, before its manufacture and delivery he should give a written explanation of the reason for the design change and for the product quality assurance after contract to IHI's Procuring Department to obtain its approval.

手掌 0 Oct. 08 0 3 1 Nov. 20 手掌 0 4 2 Oci. 18 SCALE 1:5

洛阳工匠软轴控制器有限公司 LUOYANG ARTISAN PUSH PULL CABLE CONTROLLER CO.,LTD

| STREET | Control | Contr PRINCIPLE (AS) TOLLINECT STREET, CONTROL CAN TRACE (AS) TOLLINECT (AS) 215 • 2111 ±0.1 1000 • 2111 ±0.2 2000 • 4111 ±22.1 | TOLERANCE | Tole



MARK			<u> </u>		
MAKK	٨	USED FOR	STROKE	В	С
(A)	3050	SHIFTING OPER. SIDE	110	310	177
В	6850	SHIFTING DRIVE SIDE	110	310	177
(c)	2600	SPLASH GUARD OPER. SIDE	5 0	173	101
0	4500	SPLASH GUARD DRIVE SIDE	50	173	101
(E)	2950	#2 TOP BRIDLE ROLL OPER. SIDE	5 0	173	101
P	4050	#2 TOP BRIDLE ROLL DRIVE SIDE	50	173	101
G	4550	#4 TOP BRIDLE ROLL OPER. SIDE	5 0	173	101
H	4300	#4 TOP BRIDLE ROLL DRIVE SIDE	5 0	173	101
(ı	6500	PINCH ROLL OPE. SIDE	130	355	201
K	2500	PINCH ROLL DRIVE SIDE	130	355	201
(ı)	8300	FRAME DRIVE SIDE	70	219	126

	ESSI		(sa) TO 6	TOLE	Listet	DIE	1212	-	(ae)	+		18CE	SYMBOLS	Ra (parka)		\vdash	_	_	_	4	51	21	
	6		31	+4	-		6	.	31	+-		18. 1	₩	Uss ha		1				í	M		2010
	34	•	121	44	. 1	•	30	•	63	•	TO	16.6	14	LASS PLAN		1			w	ł	t		- 3
	124	•	115	.14		·	63	•	125	•	10	16.1	₩	USS THAT	0.8	1							
_	315		1111	#		1							Ü	US THE		_	_		_	_			
- 1	***	•	2111	±1	. 7								V	LESS TIME						1		E241	CE.
• 1	***	•	1111	22	.1	910	ERSI				C	nce	₩.	6. 3		L				1	(frg.)	5 (1	e) /100
								111	8 251		ţŧ.	5	14	US He	2.5			110	0.1	4	l. Hide		±1. I
					-	EFER	250	07 1	10 584	Ι	±0			1 63		OTER	10	17	10 5	•	d. 514ep	-	24. 1
						•	588	•	1111		±4		Q.				10		12	1	t. 114eg		£4. 1
							910		3111	1	#1.		1 1/				20		41	ıT.	t. 1744		+4. 1

One electrophotographically repoducible copy of drawing and CAD-DATA to be delivered should be submitted immediately after conclusion of a contract.
 To be submitted to IHI's Pracurement Department.

2. The drawings to be delivered should have the following

the floppy disk.

3. One reproducible copy of the IHI's designated statement for delivery and shipping specification should be submitted. (The from will be supplied via YEC Prozering Group.)

(I) Its submittal shall be made two times: that is, 15 days before delivery (unless otherwise specified) and at delivery; at the first time to the MEC Prozering Group, and at the second time to the Macrial Control Group, and the second time to the Macrial Control Group. Gate like the detailed statuent is to be partially dead of the detailed statuent is to be partially and the second time to the Macriannia for the partially described the should be revised and submitted.)

Altering a lag
Altering and lied on the actual product.
In this respect, Iffi will supply its designated lag for the
contract work for air requested to will necessary matters on
aboutd contact the Precering Group to confirm it beforehand.

5. The decument to be submitted shall be written in English.
It may, however, be in both Japanese and English.

6. The applicable unit shall be SI unit.

7. Notes: (1) Two or more sheets of drawing are to be delivered,

the drawing are to be deli the drawing area must be unified.

(2) A space (30mm x 30mm) for document stamp should be lell at the upper part of the right lower little column.

For laws, regulations and standards, Japanese domestic laws, regulation and standards shall apply.

2. The painting color shall be a manufacture's standard color.

Per the painting color, the supplied color sample shall apply.

For the painting color, conform to IHI drawing M916812439.

For the guarantee period, the general contract or the order requisition shall apply.

4. Note: When a manufacture is to change the design (including the internal configuration of the product manufactured so far, before its manufacture and delivery he should give a written explanation of the reason for the design change and for the product quality assurance after contract to IBI's Procuring Department to obtain its approval.

To contact: INI's Procurement Department

Design : The product itself shall be of intrinsically safe design. When it is difficult to design so, a safety device (a) should be added to secure the safety.

"Safety plates: To assure the safety, safety precautions (Danger, warning, caution or notice) shall be clearly indicated by means of an aluminum plate(sat acree to be added to be added to be accorded to the safety of the safety.

The indication shall, in principle, conform to AMSI standards.

The indication shall, in principle, conform to AMSI standards.

'Instruction annual of a product constitutes a manual safety shall be provided to take adequate measures for PL Law.

'Others : Due responsibility shall be taken for a personal injury or physical damage caused by a defect of the product.

				A I
PARTICULARS	MATERIAL RE		REMARKS	PART NO.
WIRE	PURCHASE			350
WIRE	PURCHASE			351
WIRE	PURCHASE			352
WIRE	PURCHASE			353
WIRE	PURCHASE			354
WIRE	PURCHASE			3 5 5
WIRE	PURCHASE			356
WIRE	PURCHASE			357
WIRE	PURCHASE			358
WIRE	PURCHASE			359
WIRE	PURCHASE			360
	WIRE WIRE WIRE WIRE WIRE WIRE WIRE WIRE	WIRE	NTERL 100 NTERL 100	WIRE PURCHASE

0	0 3 0ct. 10		近幕		手軍	
2	0 3 Nav. 26		梶原		手掌	
3	0 3 Dec. 9		梶原		手電	
4	0 4 Aug. 2		1. Т	/	手軍	
NO.	DATE	DESCRIPTION	DRAWN	DESIGNED	CHECKED	APPROVE


1:2

JRD ANGLE FROJECTION

洛阳工匠软轴控制器有限公司 LUOYANG ARTISAN PUSH PULL CABLE CONTROLLER CO.,LTD

> SUBSTITUTE FOR REPLACED BY REV. BO.

"Supplier" shall obtain at its costs and sypenses all licenses, permitt, formalities or other approvals from supplier's Government or other approvals from supplier's Government or and performance of the Contract. It is expressly agreed herein that "Supplier" shall be responsible for any matter (including but not limited to penalties claimed by the relevant authorities) arising out of non fulfillent of the obligations herebove.



PUSH PULL CABLE

"Supplier" shall bear their costs and expenses for licenses, possibly formalities are either approximately formalities are either approximately for the execution of the expenses and extend the expenses of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses are expenses as a supplier of the expenses and expenses are expenses as a supplier of the expenses

Document to be submilled	(2) (3) (4)	subnited and the subnit	fie be find the find	tected and	d fill the state of the state o	ong nag driller in grant in gr		. al ms sah u meonagi aed eD c tion m mitse	ball ne le e le e le e le e le e le e le	riad sh	rovhalloc be she in ord	I be une use ent how all I N srio hem sr	e e e e e e e e e e e e e e e e e e e
General natters	2.	War The sha the the sil fro	da Pu	ty fe be te re ke	to tt. tu of ias	IH ve el s ed at	pe re(lar eq	r a	od)	of	lbs era al no ece		om of er's of
1 2 2	TY MEA	SHPP											
	plier':			de	by	pro	duc	s	ljal	ili	Ly.	rule	

	S	A	F	ĺ		ľ	Y			1	E	1		S	Ų	ì	1		S																																															
•		3		P			,	i	•		,		3		,	2	1	1		i	b	į			d	f		,	b	,	4	,	,	0	d	u	0			s	e					b	i	1	i		1	, e	d			1	e	,	1	,	0	d	u	c		
	1	D	e	3	i			0				:		i	i	n		1	,	C	C	(ı	r	d	1	ı	,	¢	e		ı	i	t	h		1																						10	١,	/	0	r			
	:	S	i		•	1	•					:					f			l	y				i		1	1	1	0					l		ŧ			A	d		į	i	t	ŧ		i	ı	ı	i	i	¢													
	ı	ú	2	n	u	1	1	۱	1			:		•		S	à	1		e	t	,	,		M	e			8	u	r		ľ	•		:	1		ı	i	ı	ĺ	ı)	e	_	d	e			c	r		t	2	d		i	,	•		2	0			
	(0	t	h	e		1	8				:		•	ı	S	u	ı	ij	p	ı	i	i	•	r	•			8	b	a	I	ı		t	a	١	i	•		r	•		1	p	0	R	8	i	il	b	i						f)	r		a		,	,

1 03	
1 0ct. 31	
NO. DATE DESCRIPTION DRAWN DESIGNED CHECKED A	PPROVED
SCALE	
1:5 洛阳工匠软轴控制器有限公司 LUOYANG ARTISAN PUSH PULL CABLE CONTROLLER CO.LTD)
REY. SO.	
1	

																							1.*	٠,	101	-	٧.
•	INERS	\$10	•	(a.e.)	TOLERADO	DI	n,	510	10	(44)	Т	101	O	(CL	STMBOLS	(pale)	CIT-BIT	Г					4.	+	-	-	Ĭ.
01	ER 1.	. 5	11	TO 6	±0.1	OTE	1.1	. 5	10	10	T	1	0	11.2		LESS PLAN	(ma)	ł					+	1		1 3	١.
	6	_		11	+4.1	1.	-			11	T	1	0	1. 4	₩.			1				1	V	11	10	ıl ă	
7	10	,		121	±4.1	1	10	5	•	17	t	1	0	1.6	1	us na	1					-1		t	_		1
•	120		•	115	14.5		63	1	٠	125	ŀ		0	1. 1	₩.	LESS THAN	1.2										ķ
٠	315	,	•	1111	24.1	Т		_							Ť	URS Na		L									
•	1910	,		2111	21.2	7									∀	3. 2		Г					Т				
•	2010	•		(111	±2. 1	DII	n:	516	1	(are)	T	701	111	sct	1 ₩	LESS PLAN							6		1	isel/t	111
15	LERL	s CE	1	01 C	MELATIN	T		I	196	1 25	Ī	,	1.	5	₩.	USS THE	2.5			01	OE	11		101		±1. 8	
Г		_	_			OFF	25			10 10	Ŧ	•		•	,	25		OTE	. 11	1	, 1	50	10.	. 584	41	41. 1	_
							51	0		100	đ	;	4.		V				10			121	20	134	4.	11. 1	_
ı							100	0		111	1	•	ii.	•	1 1	-			120			(11	20.	:14	16	11. 3	_